



“MODELACIÓN DE CAUDALES RECESIVOS PARA LA CUENCA DEL RÍO LONTUÉ, ESTACIÓN ESTERO UPEO , VII REGION DEL MAULE , CHILE”.

ENZO ERICK MARTINEZ ARAYA

INGENIERO FORESTAL

RESUMEN

Este estudio tuvo como finalidad la estimación de los caudales recessivos provenientes de aguas subterráneas y la capacidad de almacenamiento de la cuenca del estero Upeo, VII Región, Chile. La información de los hidrogramas respectivos, fue aportada por la Dirección General de Aguas y corresponde a la estación Estero Upeo, en Upeo.

Se ajustaron y evaluaron dos modelos exponenciales ($Q(t) = Q_0 e^{-n(t-t_0)}$; $Q(t) = Q_0 e^{-nt}$) y uno Potencial ($Q(t) = Q_0 (1 + a * t)^{-\frac{1}{n}}$), donde Q_0 es el caudal inicial; a el coeficiente de agotamiento o recesión; n el parámetro específico y t tiempos. Los ajustes consistieron en la determinación de los coeficientes de agotamiento a partir de los lapsos de ajuste de 10, 15, 20, 24 y 48 horas. Determine el caudal recessivo inicial Q_0 , bajo dos planteamientos; uno original (2º punto de quiebre de la curva de bajada) y uno modificado (3º punto de quiebre). La evaluación y selección se realizó a partir de las predicciones hechas por los modelos, y los valores modelados se contrastaron con los reales, utilizando para ello el coeficiente de determinación, la prueba U de Mann- Whitney y el error estándar de estimación.

De los modelos estudiados, ninguno presentó buena calidad de ajuste, aunque lo

mas adecuado seria utilizar el modelo potencial. Asimismo, cabe destacar los mejores resultados que obtuvo el planteamiento modificado en la estimación de caudales subterráneos

Finalmente, se recomienda estudiar nuevos modelos que puedan dar mejor cuenta del comportamiento de los caudales recessivos en la cuenca del Estero Upeo.

SUMMARY

The purpose of this study is the estimation of recessive flow coming from underground waters and the storage capacity of estuary Upeo basin, in the 7th Region , Chile. The corresponding hydrograph information was distributed by the Water Headquarter and Estuary Upeo station , in Upeo.

They evaluated and adjusted two exponential models, ($Q(t) = Q_0 e^{-a*(t - t_0)}$) $Q(t) = Q_0 e^{-a * (t - t_0)^n}$) and one potential ($Q(t) = Q_0 (1 + a * t - z)$, where Q_0 is the initial flow; a the depletion or recession coefficient; n the specific parameter and t time. The adjustment consisted in determining the depletion coefficient from the adjustment spaces of 10, 15, 20 , 24 and 48 hours. The recessive initial flow was determined by two expositions (reports) ; the original one (2nd failing point of the falling curve) and one modified by (3rd failing point) . Evaluation and Selection were based on model prophecies The model values were compared with the real ones. The determinig coefficient , Test of U Mann-Whitney and the standard error estimation were used for this purpose. None of the studied models presented a good adjustment quality, although the most suitable would be the potential model. At the same time, it is necessary to emphasize the best results obtained by the modified exposition in the estimation of underground flows.

Finally, the study of new models is recommended, this could show better behavior of recessive flows in the Estuary Upeo Basin.